## NSN 5915-00-930-4443

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-930-4443

Overall Height:
3.565 inches
Body Length:
2.312 inches
Body Width:
2.062 inches
Body Height:
3.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.687 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Operating Tempurature Range:
-40.0/+80.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
1.03 kilohertz blank
Input Impedance Per Function W/load:
600.0 ohms blank
Output Impedance Per Function W/source Across Input:
600.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Inclosure Type: Encased
•
Encased
Encased  Mounting Facility Type And Quantity:
Encased  Mounting Facility Type And Quantity: 4 threaded stud
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:
Encased  Mounting Facility Type And Quantity: 4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:  1.0 blank  Functional Terminal Type And Quantity:
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:  1.0 blank  Functional Terminal Type And Quantity:  1 turret output 2nd function
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:  1.0 blank  Functional Terminal Type And Quantity:  1 turret output 2nd function  Specified Frequencies Of Discrimination Per Function:
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:  1.0 blank  Functional Terminal Type And Quantity:  1 turret output 2nd function  Specified Frequencies Of Discrimination Per Function:  200.00 hertz blank and 2.26 kilohertz blank and 2.762 kilohertz blank and 4.00 kilohertz blank
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:  1.0 blank  Functional Terminal Type And Quantity:  1 turret output 2nd function  Specified Frequencies Of Discrimination Per Function:  200.00 hertz blank and 2.26 kilohertz blank and 2.762 kilohertz blank and 4.00 kilohertz blank  Thread Size:
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:  1.0 blank  Functional Terminal Type And Quantity:  1 turret output 2nd function  Specified Frequencies Of Discrimination Per Function:  200.00 hertz blank and 2.26 kilohertz blank and 2.762 kilohertz blank and 4.00 kilohertz blank  Thread Size:  0.138 inches
Encased  Mounting Facility Type And Quantity:  4 threaded stud  Insertion Loss At Reference Frequency Per Function In Decibels:  1.0 blank  Functional Terminal Type And Quantity:  1 turret output 2nd function  Specified Frequencies Of Discrimination Per Function:  200.00 hertz blank and 2.26 kilohertz blank and 2.762 kilohertz blank and 4.00 kilohertz blank  Thread Size:  0.138 inches  Frequency Band Width Per Function:

Style Designator:

Rectangular terminal/terminals on one surface

## NSN 5915-00-930-4443

Low Pass Filter - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0