## NSN 5915-00-931-0133

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-931-0133

Overall Height:
2.343 inches
Body Length:
2.060 inches
Body Width:
1.020 inches
Body Height:
2.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 1.538 inches and 1.662 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.538 inches and 0.662 inches
Operating Tempurature Range:
-0.0/+60.0 degrees celsius
Reference Frequency Per Function:
2.72 kilohertz blank
Source Impedance Rating Per Function:
1.0 kilohms blank
Load Impedance Per Function:
1.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
1.5 blank
Functional Terminal Type And Quantity:
2 pin ground 3rd function
Specified Frequencies Of Discrimination Per Function:
1.00 hertz blank and 2.72 kilohertz blank and 3.405 kilohertz blank and 3.835 kilohertz blank
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
1.00 hertz blank and 2.72 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
3.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

## NSN 5915-00-931-0133

Low Pass Filter - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0