

View Online at <https://aerobasegroup.com/nsn/5915-00-931-8482>

**Overall Height:**

4.000 inches

**Body Length:**

2.010 inches

**Body Width:**

1.760 inches

**Body Height:**

3.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.250 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Operating Temperature Range:**

+15.0/+45.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

3.5 kilohertz blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

2.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 solder stud ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

3.20 kilohertz blank and 3.30 kilohertz blank and 3.70 kilohertz blank and 3.80 kilohertz blank

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

3.30 kilohertz blank and 3.70 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

16.0 blank and 3.0 blank and 3.0 blank and 16.0 blank

**Unpackaged Unit Weight:**

1.000 pounds

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

03538-77c701585 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0