

View Online at <https://aerobasegroup.com/nsn/5915-00-931-8482>

Overall Height:

4.000 inches

Body Length:

2.010 inches

Body Width:

1.760 inches

Body Height:

3.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Temperature Range:

+15.0/+45.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

3.5 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

2.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 solder stud ground 3rd function

Specified Frequencies Of Discrimination Per Function:

3.20 kilohertz blank and 3.30 kilohertz blank and 3.70 kilohertz blank and 3.80 kilohertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

3.30 kilohertz blank and 3.70 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

16.0 blank and 3.0 blank and 3.0 blank and 16.0 blank

Unpackaged Unit Weight:

1.000 pounds

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

03538-77c701585 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0