

View Online at <https://aerobasegroup.com/nsn/5915-00-931-8487>

Overall Height:

3.880 inches

Body Length:

2.560 inches

Body Width:

1.310 inches

Body Height:

3.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.810 inches

Operating Temperature Range:

+15.0/+45.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

12.05 kilohertz blank

Input Impedance Per Function W/load:

2.0 kilohms blank

Output Impedance Per Function W/source Across Input:

4.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

2 turret input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

5.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

12.005 kilohertz blank and 12.046 kilohertz blank and 12.054 kilohertz blank and 12.155 kilohertz blank

Frequency Band Width Per Function:

12.046 kilohertz blank and 12.054 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 20.0 blank and 20.0 blank and 1.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

03538-77c701587 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0