

View Online at <https://aerobasegroup.com/nsn/5915-00-931-8491>

**Overall Height:**

5.125 inches

**Body Length:**

3.000 inches

**Body Width:**

2.000 inches

**Body Height:**

4.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.250 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Operating Temperature Range:**

+0.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

8.5 kilohertz blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

8.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

9.0 blank

**Functional Terminal Type And Quantity:**

1 turret output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

7.80 kilohertz blank and 8.40 kilohertz blank and 8.60 kilohertz blank and 9.00 kilohertz blank

**Thread Size:**

0.190 inches

**Frequency Band Width Per Function:**

8.40 kilohertz blank and 8.60 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

55.0 blank and 9.0 blank and 9.0 blank and 55.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

03538-77c707913 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0