

View Online at <https://aerobasegroup.com/nsn/5915-00-931-8491>

Overall Height:

5.125 inches

Body Length:

3.000 inches

Body Width:

2.000 inches

Body Height:

4.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.250 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Temperature Range:

+0.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

8.5 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

8.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

9.0 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Specified Frequencies Of Discrimination Per Function:

7.80 kilohertz blank and 8.40 kilohertz blank and 8.60 kilohertz blank and 9.00 kilohertz blank

Thread Size:

0.190 inches

Frequency Band Width Per Function:

8.40 kilohertz blank and 8.60 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

55.0 blank and 9.0 blank and 9.0 blank and 55.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

03538-77c707913 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0