

View Online at <https://aerobasegroup.com/nsn/5915-00-932-3039>

Overall Height:

Between 0.794 inches and 0.829 inches

Body Length:

2.531 inches

Body Width:

0.552 inches

Body Height:

0.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.195 inches and 2.205 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.195 inches and 0.205 inches

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Reference Frequency Per Function:

455.0 kilohertz blank

Load Impedance Per Function:

100.0 kilohms blank

Input Impedance Per Function W/load:

100.0 kilohms blank

Output Impedance Per Function W/source Across Input:

100.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

422.00 kilohertz blank and 454.80 kilohertz blank and 455.20 kilohertz blank and 468.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

454.80 kilohertz blank and 455.20 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

50.0 blank and 3.0 blank and 3.0 blank and 50.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0