

View Online at <https://aerobasegroup.com/nsn/5915-00-932-3039>

**Overall Height:**

Between 0.794 inches and 0.829 inches

**Body Length:**

2.531 inches

**Body Width:**

0.552 inches

**Body Height:**

0.594 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.195 inches and 2.205 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.195 inches and 0.205 inches

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

455.0 kilohertz blank

**Load Impedance Per Function:**

100.0 kilohms blank

**Input Impedance Per Function W/load:**

100.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

100.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance-resistance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

422.00 kilohertz blank and 454.80 kilohertz blank and 455.20 kilohertz blank and 468.00 kilohertz blank

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

454.80 kilohertz blank and 455.20 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

50.0 blank and 3.0 blank and 3.0 blank and 50.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0