NSN 5915-00-933-2679

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-933-2679

| Overall Height: |
|---|
| 3.360 inches |
| Body Length: |
| 4.500 inches |
| Body Width: |
| 1.810 inches |
| Body Height: |
| 3.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.160 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 3.750 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+55.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.562 inches |
| Operating Tempurature Range: |
| -40.0/+71.0 degrees celsius |
| Average Life Rating In Hours: |
| 10000.0 |
| Reference Frequency Per Function: |
| 80.0 kilohertz blank |
| Source Impedance Rating Per Function: |
| 600.0 ohms blank |
| Load Impedance Per Function: |
| 600.0 ohms blank |
| Output Impedance Per Function W/source Across Input: |
| 2.0 kilohms blank |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 8.0 blank |
| Functional Terminal Type And Quantity: |
| 1 pin output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| 78.00 kilohertz blank and 79.00 kilohertz blank and 81.00 kilohertz blank and 82.00 kilohertz blank |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| |

79.00 kilohertz blank and 81.00 kilohertz blank

NSN 5915-00-933-2679

Band Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 6.0 blank and 6.0 blank and 20.0 blank

Unpackaged Unit Weight:

1.300 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0