NSN 5915-00-934-0749

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-934-0749

Overall Height:				
2.875 inches				
Body Length:				
1.688 inches				
Body Width:				
1.188 inches				
Body Height:				
2.500 inches				
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:				
1.250 inches				
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:				
0.750 inches				
Operating Tempurature Range:				
-55.0/+105.0 degrees celsius				
Reference Frequency Per Function:				
1.5 kilohertz blank				
Source Impedance Rating Per Function:				
500.0 ohms blank				
Load Impedance Per Function:				
600.0 ohms blank				
Principal Circuitry Type Per Function:				
Inductance-capacitance blank				
Mounting Facility Screw Thread Series Designator:				
Unc				
Inclosure Type:				
Hermetically sealed				
Mounting Facility Type And Quantity:				
4 threaded stud				
Insertion Loss At Reference Frequency Per Function In Decibels:				
2.0 blank				
Functional Terminal Type And Quantity:				
1 tab, solder lug output 2nd function				
Specified Frequencies Of Discrimination Per Function:				
1.00 hertz blank and 1.50 kilohertz blank and 2.25 kilohertz blank and 3.00 kilohertz blank				
Thread Size:				
0.138 inches				
Body Material:				
Metal				
Frequency Band Width Per Function:				
1.00 hertz blank and 1.50 kilohertz blank				
Discrimination At Specificationified Frequencies Per Function In Decibels:				

3.0 blank and 30.0 blank

NSN 5915-00-934-0749

Low Pass Filter - Page 2 of 2



Style	Des	igna	itor:
D 4 -		4 _	

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0