

View Online at <https://aerobasegroup.com/nsn/5915-00-936-7572>

Overall Height:

Between 5.782 inches and 5.842 inches

Body Length:

Between 10.360 inches and 10.390 inches

Body Width:

Between 3.360 inches and 3.390 inches

Body Height:

Between 4.891 inches and 4.921 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 9.235 inches and 9.265 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.735 inches and 1.765 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

103.0 kilohertz blank

Input Impedance Per Function W/load:

1.5 kilohms blank

Output Impedance Per Function W/source Across Input:

1.5 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Inclosure Type:

Encased

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

99.80 kilohertz blank and 100.25 kilohertz blank and 106.00 kilohertz blank and 109.00 kilohertz blank

Frequency Band Width Per Function:

99.80 kilohertz blank and 100.12 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

59.0 blank and 1.0 blank and 1.0 blank and 24.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

81349-milf18327-16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0