

View Online at <https://aerobasegroup.com/nsn/5915-00-937-3259>

Overall Height:

2.720 inches

Body Length:

3.800 inches

Body Width:

2.400 inches

Body Height:

2.400 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.300 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.900 inches

Operating Temperature Range:

-55.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.445 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.320 kilohertz blank and 1.4025 kilohertz blank and 1.4875 kilohertz blank and 1.570 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.4025 kilohertz blank and 1.4875 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

47.0 blank and 3.0 blank and 3.0 blank and 47.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0