

View Online at <https://aerobasegroup.com/nsn/5915-00-937-7496>

Overall Length:

3.635 inches

Body Length:

2.941 inches

Body Width:

1.535 inches

Body Height:

1.476 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.200 inches

Reference Frequency Per Function:

40.0 lead styphnate bead pulses per second

Input Impedance Per Function W/load:

50.0 ohms 1st low pass

Output Impedance Per Function W/source Across Input:

50.0 ohms 1st low pass

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd low pass

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 1st low pass

Functional Terminal Type And Quantity:

2 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

53.00 megahertz 2nd low pass and 76.00 megahertz 2nd low pass and 106.00 megahertz 2nd low pass and 200.00 megahertz 2nd low pass

Thread Size:

0.112 inches

Frequency Band Width Per Function:

30.00 megahertz 1st low pass and 50.00 megahertz 1st low pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 2nd low pass and 1.0 2nd low pass and 50.0 2nd low pass and 50.0 2nd low pass

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0