## NSN 5915-00-938-1139

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-938-1139

Overall Height:

**3.124** inches

**Body Length:** 

Between 4.875 inches and 4.999 inches

**Body Width:** 

Between 2.500 inches and 2.624 inches

**Body Height:** 

Between 2.500 inches and 2.624 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

**Operating Tempurature Range:** 

-55.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

**Reference Frequency Per Function:** 

595.0 hertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:** 

600.0 ohms blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

**Inclosure Type:** 

Encased

Insertion Loss At Reference Frequency Per Function In Decibels:

8.0 blank

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:** 

467.50 hertz blank and 552.50 hertz blank and 637.50 hertz blank and 722.50 hertz blank

**Frequency Band Width Per Function:** 

552.50 hertz blank and 637.50 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

35.0 blank and 3.0 blank and 35.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

**Test Data Document:** 

81349-milf18327-7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

-

## NSN 5915-00-938-1139

Band Pass Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0