

View Online at <https://aerobasegroup.com/nsn/5915-00-938-2634>

Body Outside Diameter:

0.375 inches

Body Height:

0.406 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

32.0 lead styphnate bead pulses per second

Source Impedance Rating Per Function:

75.0 ohms 2nd low pass

Load Impedance Per Function:

50.0 ohms 2nd low pass

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd low pass

Voltage Standing Wave Ratio Per Function:

1.5 2nd low pass

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 2nd low pass

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 megahertz 2nd low pass and 70.00 megahertz 2nd low pass and 104.50 megahertz 2nd low pass and 139.00 megahertz 2nd low pass

Body Material:

Metal

Frequency Band Width Per Function:

1.00 megahertz 2nd low pass and 70.00 megahertz 2nd low pass

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 1st low pass and 40.0 1st low pass

Voltage Standing Wave Ratio Frequency Limits Per Function:

2.0 lead styphnate bead pulses per second and 32.0 lead styphnate bead pulses per second

Style Designator:

Round terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0