

View Online at <https://aerobasegroup.com/nsn/5915-00-945-8986>

Overall Height:

2.500 inches

Body Length:

3.500 inches

Body Width:

1.781 inches

Body Height:

2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.800 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

+10.0/+40.0 degrees celsius

Reference Frequency Per Function:

463.0 kilohertz blank

Source Impedance Rating Per Function:

2.0 kilohms blank

Load Impedance Per Function:

2.0 kilohms blank

Input Impedance Per Function W/load:

2.0 kilohms blank

Output Impedance Per Function W/source Across Input:

2.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.5 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

462.50 kilohertz blank and 462.75 kilohertz blank and 463.25 kilohertz blank and 463.50 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

462.75 kilohertz blank and 463.25 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

84.0 blank and 6.0 blank and 6.0 blank and 84.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0