

View Online at <https://aerobasegroup.com/nsn/5915-00-945-8986>

**Overall Height:**

2.500 inches

**Body Length:**

3.500 inches

**Body Width:**

1.781 inches

**Body Height:**

2.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.800 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.000 inches

**Operating Temperature Range:**

+10.0/+40.0 degrees celsius

**Reference Frequency Per Function:**

463.0 kilohertz blank

**Source Impedance Rating Per Function:**

2.0 kilohms blank

**Load Impedance Per Function:**

2.0 kilohms blank

**Input Impedance Per Function W/load:**

2.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

2.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.5 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

462.50 kilohertz blank and 462.75 kilohertz blank and 463.25 kilohertz blank and 463.50 kilohertz blank

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

462.75 kilohertz blank and 463.25 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

84.0 blank and 6.0 blank and 6.0 blank and 84.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0