## NSN 5915-00-947-9706

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-947-9706

Overall Height:
1.734 inches
Body Length:
3.000 inches
Body Width:
0.688 inches
Body Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 2.540 inches and 2.560 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Operating Tempurature Range:
-30.0/+65.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
1.825 kilohertz blank
Source Impedance Rating Per Function:
6.0 kilohms blank
Load Impedance Per Function:
6.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.2 blank
Functional Terminal Type And Quantity:
1 wire lead input 1st function
Specified Frequencies Of Discrimination Per Function:
300.00 hertz blank and 3.50 kilohertz blank and 4.50 kilohertz blank and 8.00 kilohertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:
300.00 hertz blank and 3.50 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:

0.2 blank and 0.8 blank and 34.0 blank and 37.0 blank

## NSN 5915-00-947-9706

Low Pass Filter - Page 2 of 2



	Maximum	<b>Dielectric</b>	Withstanding	Dc	Voltage:
--	---------	-------------------	--------------	----	----------

100.0 volts at sea level

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0