

View Online at <https://aerobasegroup.com/nsn/5915-00-949-5751>

**Overall Height:**

2.875 inches

**Body Length:**

3.500 inches

**Body Width:**

2.000 inches

**Body Height:**

2.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Operating Temperature Range:**

+0.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

140.0 kilohertz blank

**Input Impedance Per Function W/load:**

15.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

15.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

5.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

50.00 kilohertz blank and 139.65 kilohertz blank and 140.35 kilohertz blank and 500.00 kilohertz blank

**Thread Size:**

0.164 inches

**Frequency Band Width Per Function:**

139.65 kilohertz blank and 140.35 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

**Maximum Dielectric Withstanding Dc Voltage:**

250.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on one surface

**Test Data Document:**

42498-37366 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0