

View Online at <https://aerobasegroup.com/nsn/5915-00-949-5751>

Overall Height:

2.875 inches

Body Length:

3.500 inches

Body Width:

2.000 inches

Body Height:

2.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Operating Temperature Range:

+0.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

140.0 kilohertz blank

Input Impedance Per Function W/load:

15.0 kilohms blank

Output Impedance Per Function W/source Across Input:

15.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

50.00 kilohertz blank and 139.65 kilohertz blank and 140.35 kilohertz blank and 500.00 kilohertz blank

Thread Size:

0.164 inches

Frequency Band Width Per Function:

139.65 kilohertz blank and 140.35 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Maximum Dielectric Withstanding Dc Voltage:

250.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

42498-37366 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0