

View Online at <https://aerobasegroup.com/nsn/5915-00-950-4292>

Overall Height:

2.188 inches

Body Length:

1.312 inches

Body Width:

0.719 inches

Body Height:

1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.281 inches

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

3.9 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

3.000 kilohertz blank and 3.885 kilohertz blank and 3.915 kilohertz blank and 5.000 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

3.885 kilohertz blank and 3.915 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 4.0 blank and 4.0 blank and 18.0 blank

Unpackaged Unit Weight:

6.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0