

View Online at <https://aerobasegroup.com/nsn/5915-00-950-4307>

**Overall Height:**

2.125 inches

**Body Length:**

1.312 inches

**Body Width:**

0.719 inches

**Body Height:**

1.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.281 inches

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.5 kilohertz blank

**Input Impedance Per Function W/load:**

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

600.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

100.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 3.00 kilohertz blank and 3.90 kilohertz blank and 4.00 kilohertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 3.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

4.0 blank and 4.0 blank and 35.0 blank and 35.0 blank

**Unpackaged Unit Weight:**

6.000 ounces

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0