NSN 5915-00-952-5496

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-952-5496

| Overall Length: |
|--|
| 3.968 inches |
| Overall Height: |
| 2.935 inches |
| Body Length: |
| 3.062 inches |
| Body Width: |
| 2.531 inches |
| Body Height: |
| 2.562 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.625 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 2.125 inches |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Source Impedance Rating Per Function: |
| 50.0 ohms 2nd radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 2nd radio interference |
| Power Line Frequency Rating Per Function In Hertz: |
| 65.0 2nd radio interference |
| Operating Current Rating Per Function In Amps: |
| 1.0 2nd radio interference |
| Maximum Voltage Drop Per Function: |
| 1.0 volts ac 1st radio interference |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance 2nd radio interference |
| Input Terminal Manufacturer Code: |
| 97814 |
| Input Terminal Identification: |
| 8001-16-10p-fp |
| Maximum Tempurature Rise: |
| 25.0 degrees celsius |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |

Functional Terminal Type And Quantity:

Tunctional Terminal Type And Quantity

2 tab, solder lug output 2nd function

NSN 5915-00-952-5496

Radio Frequency Interference Filter - Page 2 of 2



Operating Voltage Rating And Type Per Function: 230.0 volts ac 2nd radio interference 2nd function Thread Size: 0.138 inches Body Material: Metal Body Surface Treatment: Tin Style Designator: Rectangular terminal/terminals on two surfaces Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A047b0