

View Online at <https://aerobasegroup.com/nsn/5915-00-953-5122>

**Overall Length:**

2.375 inches

**Overall Height:**

0.812 inches

**Body Length:**

1.875 inches

**Body Width:**

0.500 inches

**Body Height:**

0.812 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.375 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Reference Frequency Per Function:**

20.550 megahertz blank

**Source Impedance Rating Per Function:**

2.0 kilohms blank

**Load Impedance Per Function:**

2.0 kilohms blank

**Input Impedance Per Function W/load:**

2.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

2.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance-resistance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

50.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

20.450 megahertz blank and 20.650 megahertz blank and 20.525 megahertz blank and 20.575 megahertz blank

**Thread Size:**

0.086 inches

**Frequency Band Width Per Function:**

20.550 megahertz blank and 20.575 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

**Maximum Dielectric Withstanding Dc Voltage:**

5.0 volts at sea level

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0