

View Online at <https://aerobasegroup.com/nsn/5915-00-953-5122>

Overall Length:

2.375 inches

Overall Height:

0.812 inches

Body Length:

1.875 inches

Body Width:

0.500 inches

Body Height:

0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.375 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Reference Frequency Per Function:

20.550 megahertz blank

Source Impedance Rating Per Function:

2.0 kilohms blank

Load Impedance Per Function:

2.0 kilohms blank

Input Impedance Per Function W/load:

2.0 kilohms blank

Output Impedance Per Function W/source Across Input:

2.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

50.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

20.450 megahertz blank and 20.650 megahertz blank and 20.525 megahertz blank and 20.575 megahertz blank

Thread Size:

0.086 inches

Frequency Band Width Per Function:

20.550 megahertz blank and 20.575 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Maximum Dielectric Withstanding Dc Voltage:

5.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0