

View Online at <https://aerobasegroup.com/nsn/5915-00-954-3024>

Overall Height:

1.375 inches

Body Length:

1.485 inches

Body Width:

0.860 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.785 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Reference Frequency Per Function:

251.030 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

250.03 kilohertz blank and 250.98 kilohertz blank and 251.08 kilohertz blank and 252.03 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

250.98 kilohertz blank and 251.08 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

50.0 blank and 1.0 blank and 1.0 blank and 50.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0