

View Online at <https://aerobasegroup.com/nsn/5915-00-962-8494>

**Overall Height:**

Between 2.813 inches and 2.936 inches

**Body Length:**

Between 1.157 inches and 1.219 inches

**Body Width:**

Between 1.157 inches and 1.219 inches

**Body Height:**

Between 2.469 inches and 2.581 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.219 inches and 1.281 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.719 inches and 0.781 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.25 kilohertz blank

**Input Impedance Per Function W/load:**

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

600.0 ohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Uninclosed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

400.00 hertz blank and 500.00 hertz blank and 2.00 kilohertz blank and 5.00 kilohertz blank

**Thread Size:**

0.138 inches

**Frequency Band Width Per Function:**

500.00 hertz blank and 2.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 4.0 blank and 4.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0