

View Online at <https://aerobasegroup.com/nsn/5915-00-962-8494>

Overall Height:

Between 2.813 inches and 2.936 inches

Body Length:

Between 1.157 inches and 1.219 inches

Body Width:

Between 1.157 inches and 1.219 inches

Body Height:

Between 2.469 inches and 2.581 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.219 inches and 1.281 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.719 inches and 0.781 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.25 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Uninclosed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

400.00 hertz blank and 500.00 hertz blank and 2.00 kilohertz blank and 5.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

500.00 hertz blank and 2.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 4.0 blank and 4.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0