

View Online at <https://aerobasegroup.com/nsn/5915-00-975-9917>

Overall Length:

Between 1.985 inches and 2.015 inches

Overall Height:

0.590 inches

Overall Width:

1.665 inches

Body Length:

1.510 inches

Body Width:

Between 1.485 inches and 1.515 inches

Unthreaded Mounting Hole Diameter:

Between 0.141 inches and 0.155 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.750 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Temperature Range:

-55.0/+95.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 3rd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

420.0 3rd radio interference

Operating Current Rating Per Function In Amps:

0.75 1st radio interference

Maximum Voltage Drop Per Function:

400.0 millivolts ac 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd radio interference

Input Terminal Manufacturer Code:

20093

Input Terminal Identification:

Aaas-60t-l4x

Output Terminal Manufacturer Code:

20093

Output Terminal Identification:

Aaas-60t-l4x

Maximum Temperature Rise:

30.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.1 and 0.5 and 1.0 and 5.0 and 10.0 and 20.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

20.0 and 50.0 and 60.0 and 80.0 and 70.0 and 60.0

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

3 unthreaded hole

Functional Terminal Type And Quantity:

3 tab, solder lug input 1st function

Operating Voltage Rating And Type Per Function:

28.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Unpackaged Unit Weight:

5.000 ounces

Style Designator:

Rectangular terminal/terminals on adjacent surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0