

View Online at <https://aerobasegroup.com/nsn/5915-00-978-4108>

Overall Length:

5.938 inches

Body Length:

Between 3.813 inches and 3.937 inches

Body Outside Diameter:

Between 1.188 inches and 1.312 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Average Life Rating In Hours:

250.0

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

10.0 blank and 10.0 blank

Maximum Voltage Drop Per Function:

0.5 volts ac blank and 0.5 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank and 400.0 volts dc blank

Thread Size:

0.500 inches

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

81349-milf15733-2e specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0