

View Online at <https://aerobasegroup.com/nsn/5915-00-978-4118>

**Overall Height:**

0.688 inches

**Body Length:**

2.000 inches

**Body Width:**

1.000 inches

**Body Height:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.424 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.624 inches

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.8 kilohertz blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1.0 kilohms blank

**Err Default:**

Err default

**Screw Thread Diameter:**

0.112 inches

**Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Screw Thread Qty Per Inch (tpi):**

40

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.0 blank

**Functional Terminal Type And Quantity:**

1 wire lead input 1st function

**Specified Frequencies Of Discrimination Per Function:**

600.00 hertz blank and 3.00 kilohertz blank and 7.00 kilohertz blank and 100.00 kilohertz blank

**Frequency Band Width Per Function:**

600.00 hertz blank and 3.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

2.0 blank and 2.0 blank and 60.0 blank and 60.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0