

View Online at <https://aerobasegroup.com/nsn/5915-00-978-4118>

Overall Height:

0.688 inches

Body Length:

2.000 inches

Body Width:

1.000 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.424 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.624 inches

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

1.8 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Err Default:

Err default

Screw Thread Diameter:

0.112 inches

Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Screw Thread Qty Per Inch (tpi):

40

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function

Specified Frequencies Of Discrimination Per Function:

600.00 hertz blank and 3.00 kilohertz blank and 7.00 kilohertz blank and 100.00 kilohertz blank

Frequency Band Width Per Function:

600.00 hertz blank and 3.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

2.0 blank and 2.0 blank and 60.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0