NSN 5915-00-981-1569

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-981-1569

Body Length:
3.250 inches
Body Width:
0.562 inches
Body Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.938 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Reference Frequency Per Function:
1.7 kilohertz blank
Input Impedance Per Function W/load:
5.0 kilohms blank
Output Impedance Per Function W/source Across Input:
5.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
1.5 blank
Functional Terminal Type And Quantity:
5 tab, solder lug output 2nd function
Specified Frequencies Of Discrimination Per Function:
$400.00\;\text{hertz blank and}\;3.00\;\text{kilohertz blank}\;\text{and}\;21.00\;\text{kilohertz}\;\text{blank}\;\text{and}\;300.00\;\text{kilohertz}\;\text{blank}$
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:
400.00 hertz blank and 3.00 kilohertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
1.0 blank and 1.0 blank and 60.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-00-981-1569

Low Pass Filter - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0