

View Online at <https://aerobasegroup.com/nsn/5915-00-981-2774>

Overall Length:

Between 4.915 inches and 5.015 inches

Overall Height:

3.300 inches

Body Length:

4.490 inches

Body Height:

2.940 inches

Unthreaded Mounting Hole Diameter:

0.147 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.715 inches and 4.735 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-40.0/+71.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

36.0 kilohertz blank

Source Impedance Rating Per Function:

75.0 ohms blank

Load Impedance Per Function:

75.0 ohms blank

Input Impedance Per Function W/load:

75.0 ohms blank

Output Impedance Per Function W/source Across Input:

75.0 ohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.7 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

12.30 kilohertz blank and 59.70 kilohertz blank and 440.00 kilohertz blank and 4.00 megahertz blank

Frequency Band Width Per Function:

12.30 kilohertz blank and 59.70 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.7 blank and 0.7 blank and 60.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

00724-08-00487-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0