## NSN 5915-00-981-2774

Low Pass Filter - Page 1 of 2

Between 4.915 inches and 5.015 inches

12.30 kilohertz blank and 59.70 kilohertz blank

0.7 blank and 0.7 blank and 60.0 blank and 60.0 blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

**Overall Length:** 

Overall Height: 3.300 inches Body Length: 4.490 inches



View Online at https://aerobasegroup.com/nsn/5915-00-981-2774

**Body Height:** 2.940 inches **Unthreaded Mounting Hole Diameter:** 0.147 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 4.715 inches and 4.735 inches **Vibration Resistance Range In Hertz:** +10.0/+55.0 **Operating Tempurature Range:** -40.0/+71.0 degrees celsius **Average Life Rating In Hours:** 10000.0 **Reference Frequency Per Function:** 36.0 kilohertz blank **Source Impedance Rating Per Function:** 75.0 ohms blank **Load Impedance Per Function:** 75.0 ohms blank Input Impedance Per Function W/load: 75.0 ohms blank **Output Impedance Per Function W/source Across Input:** 75.0 ohms blank **Inclosure Type:** Hermetically sealed **Mounting Facility Type And Quantity:** 2 unthreaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.7 blank **Functional Terminal Type And Quantity:** 1 pin output 2nd function **Specified Frequencies Of Discrimination Per Function:** 12.30 kilohertz blank and 59.70 kilohertz blank and 440.00 kilohertz blank and 4.00 megahertz blank **Frequency Band Width Per Function:** 

## NSN 5915-00-981-2774

Low Pass Filter - Page 2 of 2



Styl	e D	esig	ınat	or

Rectangular terminal/terminals on opposite surfaces

## **Test Data Document:**

00724-08-00487-000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0