

View Online at https://aerobasegroup.com/nsn/5915-00-985-3810

| Overall Length: |
|--|
| 1.926 inches |
| Body Length: |
| 1.688 inches |
| Body Outside Diameter: |
| 0.670 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+2000.0 |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Operating Current Rating Per Function In Amps: |
| 1.0 blank |
| Maximum Voltage Drop Per Function: |
| 0.2 volts dc blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Maximum Tempurature Rise: |
| 25.0 degrees celsius |
| Mounting Facility Screw Thread Series Designator: |
| Unf |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Features Provided: |
| Nut and washer |
| Functional Terminal Type And Quantity: |
| 1 tab, solder lug output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 100.0 volts dc blank |
| Thread Size: |
| 0.312 inches |
| Body Material: |
| Metal |
| Maximum Dielectric Withstanding Dc Voltage: |
| 200.0 volts at sea level and 125.0 volts at altitude |
| Style Designator: |
| Round terminal/terminals on opposite surfaces |
| |

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0