

View Online at <https://aerobasegroup.com/nsn/5915-00-989-4861>

Overall Height:

5.000 inches

Body Length:

2.250 inches

Body Width:

2.125 inches

Body Height:

4.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.700 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.050 inches

Operating Temperature Range:

+15.0/+45.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

5.1 kilohertz blank

Input Impedance Per Function W/load:

2.0 kilohms blank

Output Impedance Per Function W/source Across Input:

2.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

7.7 blank

Functional Terminal Type And Quantity:

2 solder stud input and 2 solder stud output

Specified Frequencies Of Discrimination Per Function:

4.965 kilohertz blank and 5.035 kilohertz blank and 5.165 kilohertz blank and 5.235 kilohertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

5.035 kilohertz blank and 5.165 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

12.0 blank and 1.2 blank and 1.2 blank and 12.0 blank

Unpackaged Unit Weight:

11.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

03538-77c701594 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0