

View Online at <https://aerobasegroup.com/nsn/5915-00-992-0313>

**Overall Length:**

1.907 inches

**Body Length:**

1.281 inches

**Body Outside Diameter:**

0.702 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

60.0 blank

**Operating Current Rating Per Function In Amps:**

0.3 blank and 0.3 blank

**Maximum Voltage Drop Per Function:**

3.2 volts ac blank and 3.2 volts dc blank

**Principal Circuitry Type Per Function:**

Capacitance-inductance blank

**Full Load Insertion Loss Frequencies In Megahertz:**

0.014 and 0.03 and 0.06 and 0.1 and 0.15 and 0.3 and 0.6 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

4.0 and 19.0 and 33.0 and 43.0 and 51.0 and 65.0 and 65.0 and 65.0 and 65.0 and 45.0 and 25.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

140.0 volts ac blank and 140.0 volts dc blank

**Thread Size:**

0.250 inches

**Special Features:**

Inductor at mounting end

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0