

View Online at <https://aerobasegroup.com/nsn/5915-00-992-0313>

Overall Length:

1.907 inches

Body Length:

1.281 inches

Body Outside Diameter:

0.702 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

60.0 blank

Operating Current Rating Per Function In Amps:

0.3 blank and 0.3 blank

Maximum Voltage Drop Per Function:

3.2 volts ac blank and 3.2 volts dc blank

Principal Circuitry Type Per Function:

Capacitance-inductance blank

Full Load Insertion Loss Frequencies In Megahertz:

0.014 and 0.03 and 0.06 and 0.1 and 0.15 and 0.3 and 0.6 and 1.0 and 10.0 and 1000.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

4.0 and 19.0 and 33.0 and 43.0 and 51.0 and 65.0 and 65.0 and 65.0 and 65.0 and 45.0 and 25.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

140.0 volts ac blank and 140.0 volts dc blank

Thread Size:

0.250 inches

Special Features:

Inductor at mounting end

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0