

View Online at <https://aerobasegroup.com/nsn/5915-00-994-7046>

Overall Height:

Between 1.938 inches and 2.187 inches

Body Length:

Between 1.250 inches and 1.312 inches

Body Width:

Between 1.250 inches and 1.312 inches

Body Height:

Between 1.625 inches and 1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.234 inches and 1.266 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.234 inches and 1.266 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

75.0 kilohertz blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

15.00 kilohertz blank and 50.00 kilohertz blank and 100.00 kilohertz blank and 150.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

50.00 kilohertz blank and 100.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 0.5 blank and 0.5 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-18327/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0