NSN 5915-00-994-7724



High Pass Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5915-00-994-7724 **Overall Height:** 2.687 inches **Body Length:** 1.500 inches **Body Width:** 1.375 inches **Body Height:** 2.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.000 inches **Operating Tempurature Range:** +0.0/+50.0 degrees celsius **Average Life Rating In Hours:** 2000.0 **Reference Frequency Per Function:** 80.0 kilohertz blank **Source Impedance Rating Per Function:** 5.0 kilohms blank **Load Impedance Per Function:** 5.0 kilohms blank **Principal Circuitry Type Per Function:** Inductance-capacitance blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Hermetically sealed **Mounting Facility Type And Quantity:** 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:

Functional Terminal Type And Quantity:

1 wire hook output 2nd function

Specified Frequencies Of Discrimination Per Function:

50.00 hertz blank and 100.00 hertz blank and 20.00 kilohertz blank and 350.00 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

20.00 kilohertz blank and 350.00 kilohertz blank

NSN 5915-00-994-7724

High Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 60.0 blank and 0.5 blank and 0.5 blank

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Unpackaged Unit Weight:

6.000 ounces

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0