

View Online at <https://aerobasegroup.com/nsn/5915-00-994-7730>

**Overall Height:**

Between 3.188 inches and 3.562 inches

**Body Length:**

Between 1.969 inches and 2.031 inches

**Body Width:**

Between 1.969 inches and 2.031 inches

**Body Height:**

Between 2.875 inches and 3.125 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.355 inches and 1.395 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.355 inches and 1.395 inches

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**Average Life Rating In Hours:**

2000.0

**Reference Frequency Per Function:**

505.0 hertz blank

**Source Impedance Rating Per Function:**

250.0 ohms blank

**Load Impedance Per Function:**

5.0 kilohms blank

**Input Impedance Per Function W/load:**

250.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

5.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.0 blank

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

10.00 hertz blank and 1.00 kilohertz blank and 20.00 kilohertz blank and 350.00 kilohertz blank

**Thread Size:**

0.164 inches

**Frequency Band Width Per Function:**

10.00 hertz blank and 1.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

2.0 blank and 2.0 blank and 40.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0