

View Online at <https://aerobasegroup.com/nsn/5915-00-995-2559>

Overall Height:

2.220 inches

Body Length:

1.187 inches

Body Width:

1.187 inches

Body Height:

1.970 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.812 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

Operating Temperature Range:

-20.0/+55.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

400.0 hertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

6.2 kilohms blank

Output Impedance Per Function W/source Across Input:

6.2 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.7 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

200.00 hertz blank and 370.00 hertz blank and 430.00 hertz blank and 800.00 hertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

370.00 hertz blank and 430.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

25.0 blank and 1.7 blank and 1.7 blank and 25.0 blank

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0