

View Online at <https://aerobasegroup.com/nsn/5915-00-995-2559>

**Overall Height:**

2.220 inches

**Body Length:**

1.187 inches

**Body Width:**

1.187 inches

**Body Height:**

1.970 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.812 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.812 inches

**Operating Temperature Range:**

-20.0/+55.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

400.0 hertz blank

**Source Impedance Rating Per Function:**

600.0 ohms blank

**Load Impedance Per Function:**

600.0 ohms blank

**Input Impedance Per Function W/load:**

6.2 kilohms blank

**Output Impedance Per Function W/source Across Input:**

6.2 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance-resistance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.7 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

200.00 hertz blank and 370.00 hertz blank and 430.00 hertz blank and 800.00 hertz blank

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

370.00 hertz blank and 430.00 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

25.0 blank and 1.7 blank and 1.7 blank and 25.0 blank

**Maximum Dielectric Withstanding Dc Voltage:**

1.0 kilovolts at sea level

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0