

View Online at <https://aerobasegroup.com/nsn/5915-00-995-3820>

Overall Height:

Between 5.063 inches and 5.250 inches

Body Length:

Between 3.437 inches and 3.562 inches

Body Width:

Between 2.937 inches and 3.062 inches

Body Height:

Between 4.750 inches and 4.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.609 inches and 2.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.109 inches and 2.125 inches

Operating Temperature Range:

-0.0/+65.0 degrees celsius

Reference Frequency Per Function:

9.33 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Voltage Standing Wave Ratio Per Function:

18.0 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.5 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Specified Frequencies Of Discrimination Per Function:

7.60 hertz blank and 11.00 hertz blank and 27.00 hertz blank and 500.00 hertz blank

Thread Size:

0.164 inches

Frequency Band Width Per Function:

7.60 hertz blank and 11.00 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

2.5 blank and 2.5 blank and 36.0 blank and 36.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

7.6 hertz blank and 11.0 hertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0