

View Online at <https://aerobasegroup.com/nsn/5915-00-995-3820>

**Overall Height:**

Between 5.063 inches and 5.250 inches

**Body Length:**

Between 3.437 inches and 3.562 inches

**Body Width:**

Between 2.937 inches and 3.062 inches

**Body Height:**

Between 4.750 inches and 4.875 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.609 inches and 2.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.109 inches and 2.125 inches

**Operating Temperature Range:**

-0.0/+65.0 degrees celsius

**Reference Frequency Per Function:**

9.33 hertz blank

**Source Impedance Rating Per Function:**

10.0 kilohms blank

**Load Impedance Per Function:**

10.0 kilohms blank

**Input Impedance Per Function W/load:**

10.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

10.0 kilohms blank

**Voltage Standing Wave Ratio Per Function:**

18.0 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.5 blank

**Functional Terminal Type And Quantity:**

1 turret output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

7.60 hertz blank and 11.00 hertz blank and 27.00 hertz blank and 500.00 hertz blank

**Thread Size:**

0.164 inches

**Frequency Band Width Per Function:**

7.60 hertz blank and 11.00 hertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

2.5 blank and 2.5 blank and 36.0 blank and 36.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

7.6 hertz blank and 11.0 hertz blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0