NSN 5915-00-996-1018

Band Suppression Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-996-1018

Overall Height:
3.500 inches
Body Length:
5.062 inches
Body Width:
2.562 inches
Body Height:
3.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.000 inches
Operating Tempurature Range:
+0.0/+50.0 degrees celsius
Average Life Rating In Hours:
2000.0
Reference Frequency Per Function:
85.0 hertz blank
Source Impedance Rating Per Function:
5.0 kilohms blank
Load Impedance Per Function:
5.0 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
80.0 blank
Functional Terminal Type And Quantity:
1 wire hook output 2nd function
Specified Frequencies Of Discrimination Per Function:
30.00 hertz blank and 80.75 hertz blank and 89.25 hertz blank and 300.00 hertz blank
Thread Size:
0.164 inches
Frequency Band Width Per Function:
80.75 hertz blank and 89.25 hertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 80.0 blank and 80.0 blank and 1.0 blank

NSN 5915-00-996-1018

Band Suppression Filter - Page 2 of 2



Maximum Dielectric Withstanding Dc Voltage	Maximum	Dielectric	Withstanding	Dc	Voltage:
--	---------	-------------------	--------------	----	----------

100.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0