

View Online at <https://aerobasegroup.com/nsn/5915-00-999-4496>

Overall Height:

2.875 inches

Body Length:

1.688 inches

Body Width:

1.188 inches

Body Height:

2.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Reference Frequency Per Function:

500.0 hertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Input Impedance Per Function W/load:

540.0 ohms blank

Output Impedance Per Function W/source Across Input:

540.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 1.00 kilohertz blank and 3.75 kilohertz blank and 7.50 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

1.00 hertz blank and 1.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

0.5 blank and 0.5 blank and 35.0 blank and 35.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0