## NSN 5915-00-999-4497

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-999-4497

Overall Height:
1.453 inches
Body Length:
3.375 inches
Body Width:
2.000 inches
Body Height:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.969 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
60.0 kilohertz blank
Source Impedance Rating Per Function:
75.0 ohms blank
Load Impedance Per Function:
75.0 ohms blank
Input Impedance Per Function W/load:
75.0 ohms blank
Output Impedance Per Function W/source Across Input:
75.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
2.00 kilohertz blank and 4.00 kilohertz blank and 12.00 kilohertz blank and 108.00 kilohertz blank
Thread Size:
0.112 inches

\_ \_ \_ \_ \_

Frequency Band Width Per Function:

12.00 kilohertz blank and 108.00 kilohertz blank

## NSN 5915-00-999-4497

High Pass Filter - Page 2 of 2



## Discrimination At Specificationified Frequencies Per Function In Decibels:

50.0 blank and 45.0 blank and 0.5 blank and 0.5 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0